


Production Informations

- Output up to 250W
- High efficiency
- Long lifetime
- E40 screw base for simple lamp handling

Application Areas

- Factories and workshops
- Sport halls and multi-purpose halls
- Industrial installations
- Docks and port facilities
- Marshaling yards, container transshipment facilities
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaries



DATA SHEET



Energy

- Power (Rated)(Nom): **250W**
- Luminous Efficacy(Rated)(Nom): **88lm/W**
- Energy Efficiency Label(EEL) : **F**
- Dimmable : **No**



Substances

- Mercury (Hg) Content (Nom) : **18.0mg**



Lifetimes

- Life To 10% Failures (Nom) : **6000h**
- Life To 20% Failures (Nom) : **10000h**
- Life To 50% Failures (Nom) : **20000h**

Product Datasheet

Product Code	MHT250E4040
Nominal Watt	250W
Lamp Voltage	115-140V
Lamp Current	2.15A
Rated Lumen	22000lm
Rated Lamp Efficacy	88lm/w
Color Rendering Index (Ra)	≥20
Color Temperature	4100K□
Average Rated Lifetime	20,000hrs
Mercury Content	18mg
Energy Efficiency Class (EEC)	F
Operating Position	universal
Dimmable	no
Min Starting Temp	-40 °C
Bulb Type	T46 clear
Glass	hard glass
Lamp Base	E40
Lamp Weight	152g
Diameter	46mm
Max of Length(MOL)	257mm
Light Centre of Length(LCL)	158mm
Beam Angle	360°
Master Carton Size	27*21*28cm
QTY in Carton	20pcs/ctn
Net Weight	3.0kg/ctn
Gross Weight	4.0kg/ctn