




## BAB91-63L

### Miniature Circuit Breaker (MCB)



Model	BAB91-63L
Rated Current (In)	2, 4, 6, 10, 16, 20, 25, 32, 40, 50, 63 A
Number of Poles	1P
Rated Voltage (Un)	AC 230(240)/400(415) V
Rated Insulation Voltage (Ui)	500 V
Rated Impulse Withstand Voltage (Uimp)	4 kV
Rated Frequency	50(60) Hz
Rated Breaking Capacity (Icn)	4.5 kA
Tripping Curve	B, C, D
Magnetic Release	B curve: between 3 and 5 In C curve: between 5 and 10 In D curve: between 10 and 20 In
Electrical Endurance	4,000
Mechanical Endurance	10,000
Terminal protection	IP20
Energy Limiting Class	3
Protection Degree	2
Ambient Temperature	-5 +40 °C
Storage Temperature	-25 +55 °C
Contact Position Indication	Yes
Operation Indication Mark	Yes
Connection Terminal	Screw Terminals (Top/Bottom)
Terminal Connection Type	Cable
Terminal Size Top/Bottom for Cable	1~25mm <sup>2</sup> (17~3 AWG)
Tightening Torque	2 Nm (18 In-lbs.)
Installation	DIN Rail 35mm EN 60715
Standards	IEC/EN 60898-1 IEC/EN 60947-2
Certificate	CE



**BAB91-63L • MCB • 1P • ~ 230/400 V • 4.5 kA • 1M**

DY02060066	Μικροαυτόματη ασφάλεια / MCB 2A	1M	12/120
DY02060068	Μικροαυτόματη ασφάλεια / MCB 4A	1M	12/120
DY02060070	Μικροαυτόματη ασφάλεια / MCB 6A	1M	12/120
DY02060072	Μικροαυτόματη ασφάλεια / MCB 10A	1M	12/120
DY02060074	Μικροαυτόματη ασφάλεια / MCB 16A	1M	12/120
DY02060075	Μικροαυτόματη ασφάλεια / MCB 20A	1M	12/120
DY02060076	Μικροαυτόματη ασφάλεια / MCB 25A	1M	12/120
DY02060077	Μικροαυτόματη ασφάλεια / MCB 32A	1M	12/120
DY02060078	Μικροαυτόματη ασφάλεια / MCB 40A	1M	12/120
DY02060079	Μικροαυτόματη ασφάλεια / MCB 50A	1M	12/120
DY02060080	Μικροαυτόματη ασφάλεια / MCB 63A	1M	12/120

