

## LED LINEAR LUMINAIRE

HIGH OUTPUT SERIES

Code:

**OROS16440HO2C**

**5 YEARS**  
GUARANTEE

**TRIDONIC**



### Technical Data

Housing Material **Anodised Aluminum**

Optic Material **Opal Silicone**

Color **Upon Request**


Input Voltage **230V AC**

Input Frequency **50~60Hz**

Total Wattage **164W**

LED Type **SMD LED MODULE**

Lifespan **72.000 hours**

Protection Class **CLASS I** 

Ingress Protection **IP20**

Ambient Temperature Range **-20° ~ +50°**

LED Driver **Included**

Dimming **No**

Replaceable LED / Driver **Yes / Yes**

DRIVER BOX (400mm)



### Application

- Suitable for indoor installation

### Accessory

**ROSET55504**

- Metal linear rosette

### Photometrical Data

Color Temperature **4000K**

LED Luminous Flux **31360Lm**

Light Beam Spread **120° Symmetrical**




Lighting Transparency **50%**

Color Rendering Index (Ra) **≥80**

### Energy Data

Energy Efficiency Label **C**

Energy Consumption **164.0 kWh/1000h**



The technical data of the product may differ from the listed +/- 10%



**APOSTOLIDIS TRADING**  
Industrial area of Serres | 62100 Serres, Greece  
T. +30 23210 77020-21 | F. +30 23210 77022  
info@acalight.gr | www.acalight.gr

