

LED LINEAR LUMINAIRE

HIGH OUTPUT SERIES

Code:

OROS24940HO3C

5 YEARS
GUARANTEE

TRIDONIC



Technical Data

Housing Material **Anodised Aluminum**

Optic Material **Opal Silicone**

Color **Upon Request**

Input Voltage **230V AC**

Input Frequency **50~60Hz**

Total Wattage **86W**

LED Type **SMD LED MODULE**

Lifespan **72.000 hours**

Protection Class **CLASS I** 

Ingress Protection **IP20**

Ambient Temperature Range **-20° ~ +50°**

LED Driver **Included**

Dimming **No**

Replaceable LED / Driver **Yes / Yes**

DRIVER BOX (400mm)



Application

- Suitable for indoor installation

Accessory

ROSET55504

- Metal linear rosette

Photometrical Data

Color Temperature **4000K**

LED Luminous Flux **47790Lm**

Light Beam Spread **120° Symmetrical**




Lighting Transparency **50%**

Color Rendering Index (Ra) **≥80**

Energy Data

Energy Efficiency Label **C**

Energy Consumption **249.0 kWh/1000h**



The technical data of the product may differ from the listed +/- 10%



APOSTOLIDIS TRADING
Industrial area of Serres | 62100 Serres, Greece
T. +30 23210 77020-21 | F. +30 23210 77022
info@acalight.gr | www.acalight.gr

