

LED FLOOD LUMINAIRE WITH MOTION SENSOR


2 YEARS
GUARANTEE



6m / 180°

Application

- Suitable for outdoor installation
- Suggested for general lighting applications



Height	AVR 8	CENTER 8	Diameter
1.50m	184.971x	475.771x	372.80cm
2.00m	104.051x	287.621x	497.06cm
4.00m	26.011x	66.901x	994.13cm
4.50m	20.551x	52.061x	1110.39cm
6.00m	11.561x	39.741x	1491.19cm

Technical Data

Housing Material	Die-casting Aluminum
Optic Material	Glass
Color	Black
Input Voltage	230V AC
Input Frequency	50~60Hz
Total Wattage	30W
LED Type	SMD (LM80)
Lifespan	30.000 hours
Protection Class	CLASS I
Ingress Protection	IP66
Mechanical Impact Degree	IK09
Ambient Temperature Range	-20° ~ +50°
Driver	Built-in
Dimming	No
Replaceable LED / Driver	No / No
Power Supply Cable	3*0.75mm ² (400mm)

Photometrical Data

Color Temperature	4000K
Lumen	2550Lm
Light Beam Spread	110° Symmetrical
Color Rendering Index (Ra)	≥80

Energy Data

Energy Efficiency Label	F
Energy Consumption	30.0 kWh/1000h

The technical data of the product may differ from the listed +/- 10%

